

YAMAHA V-MAX V-MAX 1200 BLACK MAX VMX 12 (1995-1996)



MOTOR/GEARKASSE

Kapacitet: 3,8 liter, Filterkapacitet: 0,3 liter

ANVEND	KLIMA
Normal	Middelhavssagtigt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Expulsa RR 15W-50	HDX 15W-40	HDX 20W-50

Skift alle 6000 km/ 12 måneder

ANVEND	KLIMA
Normal	Koldt

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Expulsa RR 10W-40	Expulsa 10W-40	HDX 10W-40

Skift alle 6000 km/ 12 måneder

AKSELDREV

Kapacitet: 0,2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
SP Gear 5015	Gearlube GL-4 80W	Gearlube GL-4 80W-90

Kontroller alle 6000 km/ 6 måneder, skift alle 24000 km/ 24 måneder

HYDRAULISK BREMSESYSYSTEM

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Skift alle 24 måneder

KØLESYSTEM

Kapacitet: 3,05 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Coolant -38 Organic NF		

Kontroller alle 6000 km/ 6 måneder, skift alle 24000 km/ 24 måneder

YAMAHA V-MAX V-MAX 1200 BLACK MAX VMX 12 (1995-1996)



FORGAFFEL

Kapacitet: 0,62 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Fork Oil RR 10

Kontroller alle 6000 km/ 6 måneder, skift alle 12000 km/ 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.