

# YAMAHA YFM GRIZZLY YFM GRIZZLY 300 (2012-2017)



## MOTOR

Kapacitet: 1,2 liter

| ANVEND | KLIMA           |
|--------|-----------------|
| Normal | Middelhavsgtigt |

| PRODUKTANBEFALING 1      | PRODUKTANBEFALING 2      | PRODUKTANBEFALING 3   |
|--------------------------|--------------------------|-----------------------|
| <b>Expulsa RR 15W-50</b> | <b>Expulsa RR 10W-40</b> | <b>Expulsa 10W-40</b> |

Skift alle 2500 km/ 6 måneder/ 160 timer

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Arktisk |

| PRODUKTANBEFALING 1     |  |  |
|-------------------------|--|--|
| <b>Expulsa RR 5W-40</b> |  |  |

Skift alle 2500 km/ 6 måneder/ 160 timer

| ANVEND         | KLIMA           |
|----------------|-----------------|
| Første Service | Middelhavsgtigt |

| PRODUKTANBEFALING 1      | PRODUKTANBEFALING 2      | PRODUKTANBEFALING 3   |
|--------------------------|--------------------------|-----------------------|
| <b>Expulsa RR 15W-50</b> | <b>Expulsa RR 10W-40</b> | <b>Expulsa 10W-40</b> |

Skift alle 320 km/ 1 måneder/ 20 timer

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Arktisk |

| PRODUKTANBEFALING 1     |  |  |
|-------------------------|--|--|
| <b>Expulsa RR 5W-40</b> |  |  |

Skift alle 320 km/ 1 måneder/ 20 timer

## REDUKTIONSGEARKASSE

Kapacitet: 1,2 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

Skift alle 5000 km/ 12 måneder/ 320 timer

| ANVEND         | KLIMA   |
|----------------|---------|
| Første Service | Moderat |

| PRODUKTANBEFALING 1         | PRODUKTANBEFALING 2                |  |
|-----------------------------|------------------------------------|--|
| <b>Gearlube GL-5 80W-90</b> | <b>Unigear HS GL-3/GL-5 80W-90</b> |  |

Skift alle 320 km/ 1 måneder/ 20 timer

# YAMAHA YFM GRIZZLY YFM GRIZZLY 300 (2012-2017)



## SLUTGEAR

Kapacitet: 0,15 liter

| ANVEND              |                          | KLIMA   |
|---------------------|--------------------------|---------|
| Normal              |                          | Moderat |
| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2      |         |
| <b>SP Gear 5015</b> | <b>Gearlube GL-4 80W</b> |         |

Skift alle 5000 km/ 12 måneder/ 320 timer

| ANVEND              |                          | KLIMA   |
|---------------------|--------------------------|---------|
| Første Service      |                          | Moderat |
| PRODUKTANBEFALING 1 | PRODUKTANBEFALING 2      |         |
| <b>SP Gear 5015</b> | <b>Gearlube GL-4 80W</b> |         |

Skift alle 320 km/ 1 måneder/ 20 timer

## HYDRAULISK BREMSESYSTEM FOR OG BAG

Kapacitet: 0-0 liter (Imellem min. og max.)

| ANVEND                           |                           | KLIMA   |
|----------------------------------|---------------------------|---------|
| Normal                           |                           | Moderat |
| PRODUKTANBEFALING 1              | PRODUKTANBEFALING 2       |         |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |         |

Kontroller alle 2500 km/ 6 måneder/ 160 timer

## KØLESYSTEM

Kapacitet: 0,94 liter (Radiator), Kapacitet: 0,25 liter (Tank)

| ANVEND                        |  | KLIMA   |
|-------------------------------|--|---------|
| Normal                        |  | Moderat |
| PRODUKTANBEFALING 1           |  |         |
| <b>Coolant -38 Organic NF</b> |  |         |

Skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.