

YAMAHA YXR RHINO YXR 700 RHINO (2008-2009)



MOTOR

Kapacitet: 2,1 liter, Filterkapacitet: 0,1 liter

ANVEND

Normal

KLIMA

Middelhavsgtigt

PRODUKTANBEFALING 1

Expulsa RR 15W-50

PRODUKTANBEFALING 2

Expulsa RR 10W-40

PRODUKTANBEFALING 3

Expulsa 10W-40

Skift alle 2400 km/ 6 måneder/ 150 timer

ANVEND

Normal

KLIMA

Arktisk

PRODUKTANBEFALING 1

Expulsa RR 5W-40

Skift alle 2400 km/ 6 måneder/ 150 timer

ANVEND

Første Service

KLIMA

Middelhavsgtigt

PRODUKTANBEFALING 1

Expulsa RR 15W-50

PRODUKTANBEFALING 2

Expulsa RR 10W-40

PRODUKTANBEFALING 3

Expulsa 10W-40

Skift alle 320 km/ 1 måneder/ 20 timer

ANVEND

Første Service

KLIMA

Arktisk

PRODUKTANBEFALING 1

Expulsa RR 5W-40

Skift alle 320 km/ 1 måneder/ 20 timer

DIFFERENTIALE

Kapacitet: 0,18 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Gearlube GL-4 80W

Skift alle 4800 km/ 12 måneder/ 300 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Gearlube GL-4 80W

Skift alle 320 km/ 1 måneder/ 20 timer

YAMAHA YXR RHINO YXR 700 RHINO (2008-2009)



SLUTGEAR

Kapacitet: 0,25 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Gearlube GL-4 80W

Skift alle 4800 km/ 12 måneder/ 300 timer

ANVEND

Første Service

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

PRODUKTANBEFALING 2

Gearlube GL-4 80W

Skift alle 320 km/ 1 måneder/ 20 timer

HYDRAULISK BREMSESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Skift alle 24 måneder

KØLESYSTEM

Kapacitet: 2,35 liter (Radiator), Kapacitet: 0,32 liter (Tank)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

Skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.