

# ZNEN ZN125/T ZN125T-7C E FALCON4



**MOTOR BN152QMI**  
Kapacitet: 0,9 liter

ANVEND  
Normal

KLIMA  
Middelhavsgtigt

PRODUKTANBEFALING 1  
**Expulsa RR 15W-50**

PRODUKTANBEFALING 2  
**Expulsa RR 10W-40**

PRODUKTANBEFALING 3  
**Expulsa 10W-40**

*Skift alle 3000 km*

ANVEND  
Første Service

KLIMA  
Middelhavsgtigt

PRODUKTANBEFALING 1  
**Expulsa RR 15W-50**

PRODUKTANBEFALING 2  
**Expulsa RR 10W-40**

PRODUKTANBEFALING 3  
**Expulsa 10W-40**

*Skift alle 1000 km/ 1 måneder*

**SLUT-REDUKTION**  
Kapacitet: 110 cm<sup>3</sup>

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Gearlube GL-4 80W-90**

PRODUKTANBEFALING 2  
**Gearlube GL-5 80W-90**

PRODUKTANBEFALING 3  
**Unigear HS GL-3/GL-5 80W-90**

*Skift alle 5000 km/ 5 måneder*

ANVEND  
Første Service

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Gearlube GL-4 80W-90**

PRODUKTANBEFALING 2  
**Gearlube GL-5 80W-90**

PRODUKTANBEFALING 3  
**Unigear HS GL-3/GL-5 80W-90**

*Skift alle 300 km*

**HYDRAULISK BREMSESYSTEM**  
Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND  
Normal

KLIMA  
Moderat

PRODUKTANBEFALING 1  
**Drauliquid-LV Super DOT 4**

PRODUKTANBEFALING 2  
**Drauliquid-S DOT 4**

*Skift alle 24 måneder*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.