

ZNEN ZN50QT ZN50QT-15A B ZNEN BOMB



MOTOR BN139QMB
Kapacitet: 0,9 liter

ANVEND
Normal

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Expulsa RR 15W-50

PRODUKTANBEFALING 2
Expulsa RR 10W-40

PRODUKTANBEFALING 3
Expulsa 10W-40

Skift alle 2500 km/ 6 måneder

ANVEND
Første Service

KLIMA
Middelhavsagtigt

PRODUKTANBEFALING 1
Expulsa RR 15W-50

PRODUKTANBEFALING 2
Expulsa RR 10W-40

PRODUKTANBEFALING 3
Expulsa 10W-40

Skift alle 300 km/ 1 måneder

SLUT-REDUKTION
Kapacitet: 110 cm³

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Gearlube GL-4 80W-90

PRODUKTANBEFALING 2
Gearlube GL-5 80W-90

PRODUKTANBEFALING 3
Unigear HS GL-3/GL-5 80W-90

Skift alle 5000 km/ 12 måneder

HYDRAULISK BREMSESYSTEM
Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2
Drauliquid-S DOT 4

Skift alle 5000 km/ 12 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.