

AIXAM - MEGA AIXAM 300 / 400 / 500 AIXAM 400 EVOLUTION (2000-2004)



ENGINE Kubota Z402
Capacity: 1,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50

Change every 5000 km

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50

Change every 1000 km

FINAL GEAR FRONT 1/1
Capacity: 0,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Gearlube GL-4 80W

PRODUCT RECOMMENDATION 3

Gearlube GL-4 80W-90

Change every 10000 km

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Gearlube GL-4 80W

PRODUCT RECOMMENDATION 3

Gearlube GL-4 80W-90

Change every 1000 km

HYDRAULIC BRAKE SYSTEM
Capacity: 0,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

Change every 12 months

AIXAM - MEGA AIXAM 300 / 400 / 500 AIXAM 400 EVOLUTION (2000-2004)

**COOLING SYSTEM**

Capacity: 2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant -38 Organic NF****PRODUCT RECOMMENDATION 2****Coolant -26***Change every 24 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.