

**APRILIA MOJITO MOJITO 150 (2002-2008)****ENGINE**

Capacity: 1 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Expulsa RR 5W-40***Change every 3000 km***USE**

Initial service

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Expulsa RR 5W-40***Change every 500 km***FINAL REDUCTION**

Capacity: 0,09 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****SP Gear 1011****PRODUCT RECOMMENDATION 2****Gearlube HS GL-5 75W-90****PRODUCT RECOMMENDATION 3****Syngear 75W-90***Change every 24000 km***USE**

Initial service

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****SP Gear 1011****PRODUCT RECOMMENDATION 2****Gearlube HS GL-5 75W-90****PRODUCT RECOMMENDATION 3****Syngear 75W-90***Change every 1000 km***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Drauliquid DOT 5.1****PRODUCT RECOMMENDATION 2****Drauliquid-LV Super DOT 4****PRODUCT RECOMMENDATION 3****Drauliquid-S DOT 4***Change every 24 months*

**APRILIA MOJITO MOJITO 150 (2002-2008)****FRONT FORK**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
<b>Perlus H 32</b>		

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*