## **APRILIA RST 1000 FUTURA RST 1000 FUTURA** (2000-2004)



ENGINE/TRANSMISSION Capacity: 3,9 liter, Filter capacity: 0,2 liter		
USE	CLI	IMATE
Normal	Ма	oderate
PRODUCT RECOMMENDATION 1		
Expulsa RR 15W-50		
Change every 7500 km/ 12 months		

HYDRAULIC BRAKE SYSTEM		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		

Check every 7500 km/ 12 months, change every 24 months

HYDRAULIC CLUTCH SYSTEM				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			

Check every 7500 km/ 12 months, change every 24 months

COOLING SYSTEM Capacity: 2,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 12 EVO	

Check every 15000 km/24 months, change every 24 months

FRONT FORK Capacity: 0,55 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Fork Oil RR 5	Perlus H 46		
Check every 15000 km, change every 22500 km			

## **APRILIA RST 1000 FUTURA RST 1000 FUTURA** (2000-2004)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.