PRODUCT RECOMMENDATION

APRILIA RXV / SXV RXV / SXV 450 (2006-2012)

ENGINE
Capacity: 1,3 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSMISSION 5

We are unable to give a standard recommendation for this component. Please contact our service department.

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**	

Check every 3000 km, change every 12 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**	

Check every 15 hours, change every 12 months

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**	

Check every 500 km

USE	CLIMATE
Severe, first change only	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**	

Check every 3 hours

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

APRILIA RXV / SXV RXV / SXV 450 (2006-2012)

COOLING SYSTEM
Capacity: 1,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 11		

Check every 3000 km

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 11		

Check every 15 hours

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 11		

Check every 500 km

USE		CLIMATE
Severe, first change only		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 11		

Check every 3 hours

FRONT FORK

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Fork Oil RR 10	**Perlus H 32**	

Change every 9000 km

USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Fork Oil RR 10	**Perlus H 32**	

Change every 45 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367