APRILIA SCARABEO SCARABEO 400 (2006-2010)



ENGINE Capacity: 1,7 liter (Dry fill), Capacity: 1,5 lit	er (Service fill)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Expulsa RR 5W-40		
Change every 10000 km		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Expulsa RR 5W-40		
Change every 1000 km		

FINAL REDUCTION Capacity: 0,25 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Gearlube HS GL-5 75W-90	Syngear 75W-90
Check every 10000 km		'
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Gearlube HS GL-5 75W-90	Syngear 75W-90
Change every 1000 km	1	1

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			
Change every 24 months				

APRILIA SCARABEO SCARABEO 400 (2006-2010)



COOLING SYSTEM Capacity: 1,7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 11	
Change every 24 months	

FRONT FORK Capacity: 230 CM3 (each side)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 32	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.