APRILIA SPORTCITY SPORTCITY 250 I.E.

(2006-2008)



ENGINE Capacity: 1,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Expulsa RR 10W-40	Expulsa 10W-40	
Check every 5000 km, change eve	rv 10000 km	

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Expulsa RR 10W-40	Expulsa 10W-40	

Change every 1000 km

FINAL REDUCTION Capacity: 0,25 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear 75W-90	

Check every 10000 km/ 12 months, change every 20000 km

SP Gear 1011	Syngear 75W-90	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Initial service		Moderate
USE		CLIMATE

Change every 1000 km

HYDRAULIC BRAKE SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
Check every 10000 km/ 12 months, ch	ange every 24 months		

KROON-OIL B.V. Postbus 149 7600 AC Almelo

APRILIA SPORTCITY SPORTCITY 250 I.E.

(2006-2008)



GREASE POINTS/NIPPLES	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
MoS2 Grease EP 2	
Check every 10000 km/ 12 months	

COOLING SYSTEM Capacity: 1,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 11		
Check every 10000 km/ 12 months, chang	e every 24 months	
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 11		
Check every 1000 km		

FRONT FORK			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Fork Oil RR 5	Perlus H 46		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.