PRODUCT RECOMMENDATION

# ARCTIC CAT 1000 SERIES MUDPRO 1000 LIMITED EPS (2015-2017)

## ENGINE
Capacity: 1,9 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

## DIFFERENTIAL FRONT (4x4)
Capacity: 0,28 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*Check every 6 months, change every 2000 miles/ 24 months*

| USE | CLIMATE |
|---|---|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*Change every 100 miles*

## DIFFERENTIAL REAR
Capacity: 0,25 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*Check every 6 months, change every 2000 miles/ 24 months*

| USE | CLIMATE |
|---|---|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** | |

*Change every 100 miles*

## HYDRAULIC BRAKE SYSTEM
Capacity: 0-0 liter (Between min and max.)

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Drauliquid-LV Super DOT 4** | **Drauliquid-S DOT 4** | |

*Change every 24 months*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# ARCTIC CAT 1000 SERIES MUDPRO 1000 LIMITED EPS (2015-2017)

| COOLING SYSTEM<br>Capacity: 3-3,3 liter | | |
|---|---|---|
| USE<br>Normal | | CLIMATE<br>Moderate |
| PRODUCT RECOMMENDATION 1<br>**Coolant -38 Organic NF** | | |
| *Change every 24 months* | | |

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367