

## ARCTIC CAT 250 SERIES 250 (2009-2009)

**ENGINE**

Capacity: 1,6 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Expulsa RR 5W-50***Change every 3 months/ 300 miles***DIFFERENTIAL REAR**

Capacity: 150 CM3

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Gearlube LS 80W-90***Change every 1500 km/ 12 months***GEARCASE**

Capacity: 600 CM3 (Dry fill), Capacity: 500 CM3 (Service fill)

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Gearlube LS 80W-90***Change every 1500 km/ 12 months***HYDRAULIC BRAKE SYSTEM****USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Drauliquid-LV Super DOT 4****PRODUCT RECOMMENDATION 2****Drauliquid-S DOT 4***Change every 24 months***COOLING SYSTEM**

Capacity: 1,6 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Coolant -38 Organic NF***Check every 100 km/ 1 months, change every 48 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

PRODUCT RECOMMENDATION

# ARCTIC CAT 250 SERIES 250 (2009-2009)



*information contained herein is subject to changes without notification.*