

ARCTIC CAT 300 SERIES 300 UTILITY (2012-2014)



ENGINE

Capacity: 1,4 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Expulsa RR 5W-50*Change every 3 months/ 300 miles*

DIFFERENTIAL REAR

Capacity: 0,15 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Check every 300 miles/ 3 months, change every 1500 miles/ 12 months*

GEARBOX 2/1

Capacity: 0,6 liter (Dry fill), Capacity: 0,5 liter (Service fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Gearlube LS 80W-90*Check every 300 miles/ 3 months, change every 1500 miles/ 12 months*

HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4*Change every 24 months*

COOLING SYSTEM

Capacity: 1,4 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF*Change every 24 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is

ARCTIC CAT 300 SERIES 300 UTILITY (2012-2014)



advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.