

# ARCTIC CAT 425/450 SERIES 425 4X4 (2011-2012)



## ENGINE

Capacity: 3,3 liter (Dry fill), Capacity: 2,8 liter (Service fill)

### USE

Normal

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-50**

### PRODUCT RECOMMENDATION 2

**Expulsa RR 10W-40***Change every 3 months/ 300 miles*

## DIFFERENTIAL FRONT (4x4)

Capacity: 275 CM3

### USE

Normal

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Change every 48 months*

## DIFFERENTIAL REAR

Capacity: 250 CM3

### USE

Normal

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90***Change every 48 months*

## HYDRAULIC BRAKE SYSTEM

### USE

Normal

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

### PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4***Change every 24 months*

## COOLING SYSTEM

Capacity: 2,9 liter

### USE

Normal

### CLIMATE

Moderate

### PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF***Change every 24 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

PRODUCT RECOMMENDATION

# ARCTIC CAT 425/450 SERIES 425 4X4 (2011-2012)



*information contained herein is subject to changes without notification.*