PRODUCT RECOMMENDATION

ARCTIC CAT 500 SERIES XR 500 (2015-2015)

ENGINE
Capacity: 2,4 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL FRONT (4x4)
Capacity: 0,28 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**

Check every 6 months, change every 2000 miles/ 24 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**

Change every 100 miles

DIFFERENTIAL REAR
Capacity: 0,25 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**

Check every 6 months, change every 2000 miles/ 24 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Gearlube GL-5 80W-90	**Unigear HS GL-3/GL-5 80W-90**

Change every 100 miles

HYDRAULIC BRAKE SYSTEM
Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**

Change every 24 months

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

ARCTIC CAT 500 SERIES XR 500 (2015-2015)

COOLING SYSTEM Capacity: 2,9 liter		
USE Normal		CLIMATE Moderate
PRODUCT RECOMMENDATION 1 **Coolant -38 Organic NF**		
Change every 24 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367