

# ARCTIC CAT 650 SERIES 650 4X4 V2 (2005-2008)



**ENGINE H2**  
Capacity: 1,8 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

**Expulsa RR 15W-50**

*Change every 3 months/ 300 miles*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-40**

PRODUCT RECOMMENDATION 2

**Expulsa RR 10W-40**

PRODUCT RECOMMENDATION 3

**Expulsa 10W-40**

*Change every 3 months/ 300 miles*

**DIFFERENTIAL FRONT (4x4)**  
Capacity: 275 CM3

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90**

*Change every 48 months*

**DIFFERENTIAL REAR**  
Capacity: 250-275 CM3

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Gearlube LS 80W-90**

*Change every 48 months*

## HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4**

*Change every 24 months*

# ARCTIC CAT 650 SERIES 650 4X4 V2 (2005-2008)

**COOLING SYSTEM**

Capacity: 2,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*