PRODUCT RECOMMENDATION

# BAOTIAN BT49QT/50QT BT49QT-7A1/2/3 SMART RIDER 50

## ENGINE 139QMA
Capacity: 0,8 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Mediterranean |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Expulsa RR 15W-50** | **Expulsa RR 10W-40** | **Expulsa 10W-40** |
| *Change every 3000 km/ 3 months* | | |

| USE | | CLIMATE |
|---|---|---|
| First change only | | Mediterranean |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Expulsa RR 15W-50** | **Expulsa RR 10W-40** | **Expulsa 10W-40** |
| *Change every 300 km* | | |

| USE | | CLIMATE |
|---|---|---|
| Second change only | | Mediterranean |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Expulsa RR 15W-50** | **Expulsa RR 10W-40** | **Expulsa 10W-40** |
| *Change every 1000 km/ 1 months* | | |

## FINAL REDUCTION
Capacity: 110 CM3

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Gearlube GL-4 80W-90** | **Gearlube GL-5 80W-90** | **Unigear HS GL-3/GL-5 80W-90** |
| *Change every 5000 km/ 5 months* | | |

## HYDRAULIC BRAKE SYSTEM
Capacity: 0-0 liter (Between min and max.)

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **Drauliquid-LV Super DOT 4** | **Drauliquid-S DOT 4** | |
| *Change every 24 months* | | |

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367