

BENELLI CAFFÉNERO CAFFÉNERO 150

(2011 AND AFTER)

**ENGINE**

Capacity: 0,8-1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Expulsa RR 10W-40

PRODUCT RECOMMENDATION 2

Expulsa 10W-40*Change every 3000 km/ 12 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Expulsa RR 10W-40

PRODUCT RECOMMENDATION 2

Expulsa 10W-40*Change every 1000 km/ 6 months***FINAL DRIVES**

Capacity: 0,13-0,15 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90**HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 5.1*Change every 20000 km/ 24 months***COOLING SYSTEM**

Capacity: 1-1,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF

PRODUCT RECOMMENDATION 2

Coolant -26*Change every 20000 km***FRONT FORK**

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

PRODUCT RECOMMENDATION

BENELLI CAFFÉNERO CAFFÉNERO 150 **(2011 AND AFTER)**



information contained herein is subject to changes without notification.