BETA EVO EVO 2T 125 (2012-2013)



ENGINE + AUTOMATIC LUBRICATION Beta				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Tornado	Scoosynth	Maestrol		

TRANSMISSION Capacity: 0,55 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Expulsa 10W-40		
Change every 1000 km/ 40 hours		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Expulsa 10W-40		
Change every 5 hours		

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			
Change every 3000 km/ 120 hours				

HYDRAULIC CLUTCH SYSTEM Capacity: 0-0 liter (Between min and max.)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			
Change every 3000 km/ 120 hours				

Change every 3000 km/ 120 hours

BETA EVO EVO 2T 125 (2012-2013)



COOLING SYSTEM Capacity: 0,6 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Coolant -38 Organic NF			
Change every 2000 km/ 80 hours			
FRONT FORK			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Fork Oil RR 5			
Change every 6000 km/ 240 hours			
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1			
Fork Oil RR 5			
Change every 1000 km/ 40 hours			
USE		CLIMATE	
Second change only		Moderate	
PRODUCT RECOMMENDATION 1			
Fork Oil RR 5			

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.