

BETA M4 4T M4 4T (2007-2016)**ENGINE**

Capacity: 2,1 liter, Capacity: 2,3 liter (Dry fill), Filter capacity: 0,2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Expulsa RR 15W-50***Change every 5000 km***USE**

Initial service

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Expulsa RR 15W-50***Change every 1000 km***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Drauliquid-LV Super DOT 4****PRODUCT RECOMMENDATION 2****Drauliquid-S DOT 4***Check every 5000 km, change every 24 months***USE**

Initial service

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Drauliquid-LV Super DOT 4****PRODUCT RECOMMENDATION 2****Drauliquid-S DOT 4***Check every 1000 km***FRONT FORK**

Capacity: 0,57 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Perlus H 32***Check every 10000 km***USE**

Initial service

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Perlus H 32***Check every 1000 km*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is

BETA M4 4T M4 4T (2007-2016)



advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.