BMW R SERIES R 1200 R 0A04/0A41 (2015-2018)



ENGINE/TRANSMISSION Capacity: 4 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Expulsa RR 5W-40			
Check every 3000 km, change every 10000 km/ 12 months			
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1			
Expulsa RR 5W-40			
Change every 500 km			

SHAFT DRIVE Capacity: 0,18 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 1011		
Change over 20000 km/24 months		

Change every 20000 km/ 24 months

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 24 months

Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
Draulinuid IV Super DOT 4	Drauliauid C DOT 4		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Initial service		Moderate	
USE		CLIMATE	

Change every 12 months

HYDRAULIC CLUTCH SYSTEM

We are unable to give a standard recommendation for this component. Please contact our service department.

BMW R SERIES R 1200 R 0A04/0A41 (2015-2018)



COOLING SYSTEM Capacity: 0-0 liter (Between min and max.)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Coolant -38 Organic NF	Coolant -26			

Check every 12 months

FRONT FORK LEFT

Capacity: 0,59 liter (Initial fill), Capacity: 0,29 liter (with electronic suspension adjustment)

We are unable to give a standard recommendation for this component. Please contact our service department.

FRONT FORK RIGHT

Capacity: 0,59 liter (Initial fill), Capacity: 0,68 liter (with electronic suspension adjustment)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.