

# BMW R SERIES R NINET 0A06/0A16 (2014-2014)

**ENGINE**

Capacity: 4 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Expulsa RR 15W-50****SHAFT DRIVE**

Capacity: 0,18 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**SP Gear 1011****TRANSMISSION 6**

Capacity: 0,8 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**SP Gear 1011****HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

## PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4****HYDRAULIC CLUTCH SYSTEM**

We are unable to give a standard recommendation for this component. Please contact our service department.

**FRONT FORK LEFT**

Capacity: 0,53 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

**FRONT FORK RIGHT**

Capacity: 0,53 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

# BMW R SERIES R NINET 0A06/0A16 (2014-2014)



*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*