

BOMBARDIER DS DS 250 (2006-2006)**ENGINE**

Capacity: 1,2 liter, Capacity: 1,4 liter (Dry fill)

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Expulsa RR 5W-50*Change every 1000 km/ 50 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Expulsa RR 5W-40*Change every 1000 km/ 50 hours*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Helar 0W-40*Change every 1000 km/ 50 hours*

USE	CLIMATE
Initial service	Tropical

PRODUCT RECOMMENDATION 1

Expulsa RR 5W-50*Change every 200 km/ 10 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Expulsa RR 5W-40*Change every 200 km/ 10 hours*

USE	CLIMATE
Initial service	Arctic

PRODUCT RECOMMENDATION 1

Helar 0W-40*Change every 200 km/ 10 hours*

BOMBARDIER DS DS 250 (2006-2006)**FINAL DRIVES**

Capacity: 2 liter (Dry fill), Capacity: 0,18 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140*Change every 4000 km/ 24 months/ 200 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140*Check every 500 km/ 25 hours***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4*Change every 4000 km/ 24 months/ 200 hours***COOLING SYSTEM**

Capacity: 0,85 liter (Radiator + engine)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15+

PRODUCT RECOMMENDATION 2

Coolant SP 12

PRODUCT RECOMMENDATION 3

Coolant -38 Organic NF*Change every 4000 km/ 24 months/ 200 hours*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.