

BRP CAN-AM RENEGADE RENEGADE 500

(2014-2014)

**ENGINE**

Capacity: 2 liter

USE	CLIMATE
Normal	Tropical

PRODUCT RECOMMENDATION 1

Expulsa RR 5W-50*Change every 3000 km/ 12 months/ 100 hours*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Expulsa RR 5W-40*Change every 3000 km/ 12 months/ 100 hours*

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Helar 0W-40*Change every 3000 km/ 12 months/ 100 hours*

USE	CLIMATE
Initial service	Tropical

PRODUCT RECOMMENDATION 1

Expulsa RR 5W-50*Change every 300 km/ 10 hours*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

Expulsa RR 5W-40*Change every 300 km/ 10 hours*

USE	CLIMATE
Initial service	Arctic

PRODUCT RECOMMENDATION 1

Helar 0W-40*Change every 300 km/ 10 hours*

BRP CAN-AM RENEGADE RENEGADE 500

(2014-2014)

**DIFFERENTIAL FRONT**

Capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear 75W-90	

Check every 1500 km/ 50 hours, change every 6000 km/ 24 months/ 200 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear 75W-90	

Check every 300 km/ 10 hours

DIFFERENTIAL REAR

Capacity: 0,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		

Change every 3000 km/ 12 months/ 100 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		

Check every 300 km/ 10 hours

GEARBOX

Capacity: 0,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		

Check every 3000 km/ 12 months/ 100 hours, change every 6000 km/ 24 months/ 200 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube Racing 75W-140		

Change every 300 km/ 10 hours

BRP CAN-AM RENEGADE RENEGADE 500

(2014-2014)



HYDRAULIC BRAKE SYSTEM

Capacity: 0,34 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 6000 km/ 24 months/ 200 hours

COOLING SYSTEM

Capacity: 3,4 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Check every 3000 km/ 12 months/ 100 hours, change every 6000 km/ 24 months/ 200 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.