BRP CAN-AM SPYDER SPYDER ST(S/LIMITED) ROADSTER SM5 (2013-2013)



ENGINE/TRANSMISSION SM5 Capacity: 3,9 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Expulsa RR 5W-40	
Change every 5000 km	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Expulsa RR 5W-40	
Change every 1000 km	

HYDRAULIC BRAKE SYSTEM Capacity: 530 CM3 (Between min and max.)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
Check every 10000 km/ 12 months, ch	ange every 20000 km/ 24 months		

COOLING SYSTEM Capacity: 3,2 liter CLIMATE Normal Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 PRODUCT RECOMMENDATION 3 Coolant SP 15+ Coolant SP 12 Coolant -38 Organic NF

Check every 5000 km, change every 20000 km/24 months

use Initial service		climate Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
Check every 1000 km	'	'

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.