BSA A65 A65 HORNET A65.H (1966-1968)



| ENGINE Capacity: 3 liter | | |
|-----------------------------|---|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Classic Monograde 50 | | |
| Change every 3200 km | | |
| USE | (| CLIMATE |
| Normal | | Arctic |
| PRODUCT RECOMMENDATION 1 | | |
| Classic Monograde 30 | | |
| Change every 3200 km | | |

| GEARBOX 4 Capacity: 0,5 liter | | | |
|-------------------------------|-----------------------------|--------------------|--|
| USE | | сымате Moderate | |
| Normal | | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Gearlube GL-4 80W-90 | Unigear HS GL-3/GL-5 80W-90 | | |

Check every 3200 km, change every 8000 km

| PRIMARY CHAINCASE Capacity: 0,14 liter | |
|--|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Classic Monograde 30 | |
| Check every 1600 km, change every 8000 | ' |

| GREASE POINTS/NIPPLES | | | | |
|--------------------------|--------------------------|--------------------------|--|--|
| USE | | CLIMATE | | |
| Normal | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | | |
| Labora Grease | Q5 MP Calcep Grease EP 2 | MP Lithep Grease EP 2 | | |

BSA A65 A65 HORNET A65.H (1966-1968)



| FRONT FORK Capacity: 0,2 liter | |
|--------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Classic Monograde 30 | |
| Change every 16000 km | · |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.