## **BUELL S3 S3T THUNDERBOLT** (1996-1999)



ENGINE Capacity: 2,37 liter, Filter capacity: 0,12 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Check every 4000 km, change every 8000 km/ 12 months		
USE		CLIMATE
Acceptable		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Bi-Turbo 15W-40	Bi-Turbo 20W-50	
1105		OLIMATE
USE		CLIMATE
Acceptable		Cold
PRODUCT RECOMMENDATION 1		
Emperol 10W-40		

## **TRANSMISSION** 5 Capacity: 0,95 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

## **HYDRAULIC BRAKE SYSTEM**

We are unable to give a standard recommendation for this component. Please contact our service department.

## FRONT FORK

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.