

CASALINI KERRY / SULKYCAR KERRY / SULKYCAR (2010 AND AFTER)



ENGINE Mitsubishi L2C
Capacity: 2,4 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 15W-40

Change every 5000 km

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 15W-40

Check every 1000 km

FINAL GEAR REAR 1/1
Capacity: 0,75 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-5 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

Change every 20000 km

HYDRAULIC BRAKE SYSTEM
Capacity: 0,25 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

Change every 30000 km/ 24 months

COOLING SYSTEM
Capacity: 4,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 12 EVO

Change every 30000 km/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.