

CFMOTO CF 800 4X4 CF 800-2 4X4 TERRALANDER X8 (2013 AND AFTER)

**ENGINE**

Capacity: 3,5 liter (Dry fill), Capacity: 3,4 liter (Service fill), Filter capacity: 0,1 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Expulsa RR 10W-40***Change every 1000 km/ 6 months/ 100 hours***USE**

Initial service

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Expulsa RR 10W-40***Change every 250 km/ 1 months***DIFFERENTIAL FRONT**

Capacity: 0,33 liter (Dry fill), Capacity: 0,28 liter (Service fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Expulsa RR 10W-40****PRODUCT RECOMMENDATION 2****Gearlube GL-4 80W-90****PRODUCT RECOMMENDATION 3****Unigear HS GL-3/GL-5 80W-90***Check every 250 km/ 1 months/ 25 hours, change every 12 months***DIFFERENTIAL REAR**

Capacity: 0,3 liter (Dry fill), Capacity: 0,25 liter (Service fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Expulsa RR 10W-40****PRODUCT RECOMMENDATION 2****Gearlube GL-4 80W-90****PRODUCT RECOMMENDATION 3****Unigear HS GL-3/GL-5 80W-90***Check every 250 km/ 1 months/ 25 hours, change every 12 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Drauliquid-LV Super DOT 4****PRODUCT RECOMMENDATION 2****Drauliquid-S DOT 4****PRODUCT RECOMMENDATION 3****Drauliquid DOT 3***Change every 24 months*

CFMOTO CF 800 4X4 CF 800-2 4X4 TERRALANDER X8 (2013 AND AFTER)

**COOLING SYSTEM**

Capacity: 1,9 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	

Check every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.