DERBI BOULEVARD BOULEVARD 150 (2004-2009)



ENGINE Capacity: 0,6 liter (Service fill)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Expulsa RR 5W-40	
Change every 6000 km/ 12 months	

FINAL REDUCTION
Capacity: 0,1 liter

USE

Normal

PRODUCT RECOMMENDATION 1

PRODUCT RECOMMENDATION 2

CLIMATE

Moderate

Gearlube GL-4 80W-90 Unigear HS GL-3/GL-5 80W-90

Change every 6000 km/ 12 months

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	Unigear HS GL-3/GL-5 80W-90	

Change every 1000 km/2 months

HYDRAULIC BRAKE SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		

Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.