## **DINLI DL 503 COBIA 50** (2011 AND AFTER)



| ENGINE + AUTOMATIC LUBRICATION Capacity: 0,65 liter |                          |                          |  |  |
|---|--------------------------|--------------------------|--|--|
| USE   |                          | CLIMATE                  |  |  |
| Normal  |                          | Moderate                 |  |  |
| PRODUCT RECOMMENDATION 1                            | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |  |  |
| Tornado   | Scoosynth                | Maestrol                 |  |  |

| FINAL REDUCTION                        |                             |          |  |
|--|-----------------------------|----------|--|
| USE                                    |                             | CLIMATE  |  |
| Normal                                 |                             | Moderate |  |
| PRODUCT RECOMMENDATION 1               | PRODUCT RECOMMENDATION 2    |          |  |
| Gearlube GL-5 80W-90                   | Unigear HS GL-3/GL-5 80W-90 |          |  |
| Change avan, 1000 km/s months/20 haura |                             |          |  |

Change every 1000 km/6 months/30 hours

| USE CLIMATE Normal Moderate PRODUCT RECOMMENDATION 1 | HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.) |          |  |  |
|--|---|----------|--|--|
| PRODUCT RECOMMENDATION 1                             | USE   | CLIMATE  |  |  |
|  | Normal  | Moderate |  |  |
|  | PRODUCT RECOMMENDATION 1  |          |  |  |
| Drauliquid DOT 3                                     | Drauliquid DOT 3  |          |  |  |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.