DINLI DL 605 DL 605 - 110 ENFORCER



ENGINE + AUTOMATIC LUBRICATION Capacity: 0,65 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Tornado	Scoosynth	Maestrol		

FINAL REDUCTION			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90		
Change ayon, 1000 km/s months/ 20 hours			

Change every 1000 km/6 months/30 hours

USE CLIMATE Normal Moderate PRODUCT RECOMMENDATION 1	HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)			
PRODUCT RECOMMENDATION 1	USE	CLIMATE		
	Normal	Moderate		
	PRODUCT RECOMMENDATION 1			
Drauliquid DOT 3	Drauliquid DOT 3			

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.