
## **DUCATI SCRAMBLER SCRAMBLER 800**





ENGINE/TRANSMISSION Capacity: 3,4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Expulsa RR 15W-50	
Change every 12000 km/ 12 months	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Expulsa RR 15W-50	
Change every 1000 km	

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and m	ax.)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Check every 12000 km/ 12 months, ch	ange every 36 months	·

HYDRAULIC CLUTCH SYSTEM
Capacity: 0-0 liter (Between min and max.)

USE

Normal

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT ABOUT AB

Check every 12000 km/ 12 months, change every 36 months

FRONT FORK Capacity: 298 CM3 (Fork leg left sid	de), Capacity: 427 CM3 (Fork leg right side)		
USE		CLIMATE	CLIMATE
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
ATF Dexron II-D	Fork Oil RR 5		
Change every 36000 km	,	1	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.