DUCATI SPORTCLASSIC GT 1000 (SPORTCLASSIC) (2008-2010)



ENGINE/TRANSMISSION Capacity: 3,7 liter		
USE	CLIMATE	
Normal	Mediterran	ean
PRODUCT RECOMMENDATION 1		
Expulsa RR 15W-50		
Change every 12000 km/ 12 months		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Expulsa RR 10W-40		
Change every 12000 km/ 12 months		
USE	CLIMATE	
Initial service	Mediterran	ean
PRODUCT RECOMMENDATION 1		
Expulsa RR 15W-50		
Change every 1000 km/ 6 months		
USE	CLIMATE	
Initial service	Moderate	
PRODUCT RECOMMENDATION 1		
Expulsa RR 10W-40		
Change every 1000 km/ 6 months		
HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)		

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and ma	ax.)		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		

Check every 1000 km/ 6 months, change every 36000 km/ 36 months

HYDRAULIC CLUTCH SYSTEM Capacity: 0-0 liter (Between min and ma	x.)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Check every 1000 km/6 months, chang	e every 36000 km/ 36 months	

DUCATI SPORTCLASSIC GT 1000 (SPORTCLASSIC) (2008-2010)



GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2
Change every 12000 km/ 12 month	hs	

FRONT FORK Capacity: 0,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
ATF Dexron II-D	Fork Oil RR 5	
Check every 1000 km/ 6 months, c	hange every 36000 km/ 36 months	,

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.