DUCATI SUPER SPORT 1000 DS CARENATA SS1000 DS CARENATA (2002-2006)



ENGINE/TRANSMISSION Capacity: 3,5-3,9 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Expulsa RR 15W-50	Expulsa RR 10W-40	

Check every 1000 km, change every 10000 km

HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 1000 km, change every 20000 km

HYDRAULIC CLUTCH SYSTEM USE CLIMATE Normal Moderate PRODUCT RECOMMENDATION 1 PRODUCT RECOMMENDATION 2 Drauliquid-LV Super DOT 4 Drauliquid-S DOT 4

Check every 1000 km, change every 20000 km

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Labora Grease	Q5 MP Calcep Grease EP 2	MP Lithep Grease EP 2

FRONT FORK Capacity: 0,53 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
ATF Dexron II-D	Fork Oil RR 5	
Change every 20000 km		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.