

**GILERA GSM 50 GSM 50 (2000-2004)****ENGINE + AUTOMATIC LUBRICATION**

Capacity: 1,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Tornado***Check every 5000 km/ 12 months, change every 10000 km/ 24 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**Tornado***Change every 1000 km/ 4 months***TRANSMISSION**

Capacity: 0,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**SP Gear 5015**

PRODUCT RECOMMENDATION 2

**Gearlube GL-4 80W***Check every 10000 km/ 24 months***HYDRAULIC BRAKE SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid-LV Super DOT 4**

PRODUCT RECOMMENDATION 2

**Drauliquid-S DOT 4***Check every 5000 km/ 12 months, change every 24 months***COOLING SYSTEM**

Capacity: 0,85 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Coolant -38 Organic NF**

PRODUCT RECOMMENDATION 2

**Coolant -26***Check every 5000 km/ 12 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.