HARLEY-DAVIDSON DYNA FLD/FXD FXDL/I DYNA LOW RIDER (2006-2006)



ENGINE Twin Cam 88 Capacity: 2,4 liter		
USE		CLIMATE
Normal (alternative)		Moderate
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Change every 8000 km		
USE		CLIMATE
Normal (preferred)		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Change every 8000 km		
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Change every 1600 km		
use Acceptable		CLIMATE Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Bi-Turbo 15W-40	Bi-Turbo 20W-50	
PRIMARY CHAINDRIVE		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Check every 8000 km		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Check every 1600 km		

HARLEY-DAVIDSON DYNA FLD/FXD FXDL/I DYNA LOW RIDER (2006-2006)



TRANSMISSION 6 Capacity: 0,95 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Bi-Turbo 20W-50	
Change every 8000 km	
USE	CLIMATE
Initial service	Moderate
PRODUCT RECOMMENDATION 1	
Bi-Turbo 20W-50	
Change every 1600 km	

HYDRAULIC BRAKE SYSTEM Capacity: 0,35 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 8000 km, change every 24 months

FRONT FORK

Capacity: 0,31 liter (each leg)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.