HARLEY-DAVIDSON DYNA FLD/FXD FXDWG/I DYNA WIDE GLIDE (2000-2005)



ENGINE Twin Cam 88 Capacity: 2,84 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Check every 4000 km, change every 8000	km/ 12 months	
USE		CLIMATE
Acceptable		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Bi-Turbo 15W-40	Bi-Turbo 20W-50	
USE		CLIMATE
Acceptable		Cold
PRODUCT RECOMMENDATION 1		
Emperol 10W-40		

PRIMARY CHAINDRIVE Capacity: 0,77 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Check every 1 months, change every 80	00 km	

TRANSMISSION 5 Capacity: 0,7 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Check every 4000 km/ 1 months, cha	inge every 8000 km	

HYDRAULIC BRAKE SYSTEM

We are unable to give a standard recommendation for this component. Please contact our service department.

HARLEY-DAVIDSON DYNA FLD/FXD FXDWG/I DYNA WIDE GLIDE (2000-2005)



PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Normal		Moderate
USE		CLIMATE

Check every 8000 km/24 months

FRONT FORK Capacity: 0,88 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 46	
Change every 16000 km/ 12 months	·

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.