

HARLEY-DAVIDSON SOFTAIL FLS/FXS

FXSTB SOFTAIL NIGHT TRAIN (1997-1999)



ENGINE Evolution
Capacity: 2,84 liter

USE	CLIMATE
Normal (alternative)	Moderate

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50

Check every 4000 km, change every 8000 km/ 12 months

USE	CLIMATE
Normal (preferred)	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50

Check every 4000 km, change every 8000 km/ 12 months

USE	CLIMATE
Acceptable	Mediterranean

PRODUCT RECOMMENDATION 1

Bi-Turbo 15W-40

PRODUCT RECOMMENDATION 2

Bi-Turbo 20W-50

USE	CLIMATE
Acceptable	Cold

PRODUCT RECOMMENDATION 1

Emperol 10W-40

PRIMARY CHAINDRIVE
Capacity: 0,77 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Expulsa RR 10W-40

PRODUCT RECOMMENDATION 2

Expulsa 10W-40

Check every 1 months, change every 8000 km

TRANSMISSION 5
Capacity: 0,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-4 80W-90

PRODUCT RECOMMENDATION 2

Unigear HS GL-3/GL-5 80W-90

Check every 4000 km/ 1 months, change every 8000 km

HARLEY-DAVIDSON SOFTAIL FLS/FXS FXSTB SOFTAIL NIGHT TRAIN (1997-1999)



HYDRAULIC BRAKE SYSTEM

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.