

HARLEY-DAVIDSON SPORTSTER XL/XR XL

1200C SPORTSTER CUSTOM (1995-1999)

**ENGINE**

Capacity: 2,84 liter

USE

Normal (alternative)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Bi-Turbo 20W-50***Check every 4000 km, change every 8000 km/ 12 months***USE**

Normal (preferred)

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Bi-Turbo 20W-50***Check every 4000 km, change every 8000 km/ 12 months***USE**

Acceptable

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1**Bi-Turbo 15W-40****PRODUCT RECOMMENDATION 2****Bi-Turbo 20W-50****USE**

Acceptable

CLIMATE

Cold

PRODUCT RECOMMENDATION 1**Emperol 10W-40****TRANSMISSION 5**

Capacity: 0,95 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Bi-Turbo 20W-50***Check every 4000 km/ 1 months, change every 8000 km***HYDRAULIC BRAKE SYSTEM**

We are unable to give a standard recommendation for this component. Please contact our service department.

HARLEY-DAVIDSON SPORTSTER XL/XR XL

1200C SPORTSTER CUSTOM (1995-1999)

**FRONT FORK**

Capacity: 0,32 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Perlus H 46		

Change every 16000 km/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.