

HARLEY-DAVIDSON SPORTSTER XL/XR XL

1200V SEVENTY TWO LF (2011-2016)



ENGINE Evolution
Capacity: 2,6 liter

| USE | CLIMATE |
|--------------------|---------------|
| Normal (preferred) | Mediterranean |

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50

Change every 8000 km

| USE | CLIMATE |
|-----------------|---------------|
| Initial service | Mediterranean |

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50

Change every 1600 km

TRANSMISSION 5
Capacity: 0,95 liter

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50

Change every 16000 km

| USE | CLIMATE |
|-----------------|----------|
| Initial service | Moderate |

PRODUCT RECOMMENDATION 1

Bi-Turbo 20W-50

Change every 1600 km

HYDRAULIC BRAKE SYSTEM
Capacity: 0-0 liter (Between min and max.)

| USE | CLIMATE |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

Check every 8000 km, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.