HARLEY-DAVIDSON SPORTSTER XL/XR XL 1200X SPORTSTER FORTY EIGHT LC (2009-2010)



ENGINE Evolution Capacity: 3,4 liter		
USE		CLIMATE
Normal (alternative)		Moderate
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Change every 8000 km		
USE		CLIMATE
Normal (preferred)		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Change every 8000 km		
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Bi-Turbo 20W-50		
Change every 1600 km		
USE		CLIMATE
Acceptable		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	

TRANSMISSION 5 Capacity: 0,95 liter	
USE	CLIMATE
Normal	Moderate

Bi-Turbo 20W-50

Bi-Turbo 20W-50

Bi-Turbo 15W-40

Change every 16000 km

PRODUCT RECOMMENDATION 1

use Initial service	climate Moderate
PRODUCT RECOMMENDATION 1	
Bi-Turbo 20W-50	
Change every 1600 km	

HARLEY-DAVIDSON SPORTSTER XL/XR XL 1200X SPORTSTER FORTY EIGHT LC (2009-2010)



HYDRAULIC BRAKE SYSTEM		
HIDRAULIC BRAKE SISIEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 8000 km, change every 24 months

FRONT FORK

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.