## HARLEY-DAVIDSON VRSC VRS VRSCDX NIGHT ROD SPECIAL (2007-2007)



ENGINE/TRANSMISSION Revolution Capacity: 4,3 liter, Capacity: 4,7 liter (Overhaul capacity)				
USE		CLIMATE		
Normal		Mediterranean		
PRODUCT RECOMMENDATION 1				
Bi-Turbo 20W-50				
Change every 8000 km				
USE		CLIMATE		
Initial service		Mediterranean		
PRODUCT RECOMMENDATION 1				
Bi-Turbo 20W-50				
Change every 1600 km				

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and m	nax.)		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
01 1 00001 1	4 4		

Check every 8000 km, change every 24 months

HYDRAULIC CLUTCH SYSTEM Capacity: 0-0 liter (Between min and m	ax.)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
Check every 8000 km, change every 2	4 months	

COOLING SYSTEM Capacity: 2,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

Change every 48000 km