HARLEY-DAVIDSON VRSC VRS VRSCR STREET ROD HCG (2007-2008)



ENGINE/TRANSMISSION Revolution 76 Capacity: 4,3 liter, Capacity: 4,7 liter (Overhaul capacity)				
USE		CLIMATE		
Normal		Mediterranean		
PRODUCT RECOMMENDATION 1				
Bi-Turbo 20W-50				
Change every 8000 km	-			
USE		CLIMATE		
Normal (alternative)		Moderate		
PRODUCT RECOMMENDATION 1				
Bi-Turbo 20W-50				
Change every 8000 km	-			
USE		CLIMATE		
Initial service		Mediterranean		
PRODUCT RECOMMENDATION 1				
Bi-Turbo 20W-50				
Change every 1600 km				
USE		CLIMATE		
Acceptable		Mediterranean		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Bi-Turbo 15W-40	Bi-Turbo 20W-50			

	CLIMATE	
	Moderate	
PRODUCT RECOMMENDATION 2		
Drauliquid-S DOT 4		
		PRODUCT RECOMMENDATION 2

Check every 8000 km, change every 24 months

HYDRAULIC CLUTCH SYSTEM Capacity: 0-0 liter (Between min and max.))			
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			

Check every 8000 km, change every 24 months

HARLEY-DAVIDSON VRSC VRS VRSCR STREET ROD HCG (2007-2008)



COOLING SYSTEM Capacity: 2,4 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	

Change every 48000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.