## HONDA CB CB 1000 R (2008-2018)



ENGINE/TRANSMISSION Capacity: 3,6 liter (Dry fill), Capacity: 3 liter (Service fill), Filter capacity: 0,3 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Expulsa 10W-40				
Change every 12000 km/ 12 months				
USE		CLIMATE		
Initial service		Moderate		
PRODUCT RECOMMENDATION 1				
Expulsa 10W-40				
Change every 1000 km				

HYDRAULIC BRAKE SYSTEM				
Capacity: 0-0 liter (Between min and max.)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			
Change avery 19000 km/ 19 months				

Change every 18000 km/ 18 months

HYDRAULIC CLUTCH SYSTEM Capacity: 0-0 liter (Between min and max.)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 18000 km/ 18 months

COOLING SYSTEM Capacity: 3,06 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 11		
Change avenue 26000 km/24 months		

Change every 36000 km/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.