## HONDA CBR CBR 400 RR (1990-1993)



ENGINE/TRANSMISSION Capacity: 3,8 liter (Dry fill), Capacity: 3,4 liter (Service fill), Filter capacity: 0,2 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Expulsa RR 10W-40	Expulsa 10W-40	HDX 10W-40		
Change every 6000 km/ 6 months				
USE		CLIMATE		
Initial service		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Expulsa RR 10W-40	Expulsa 10W-40	HDX 10W-40		

BRAKE SYSTEM iter (Between min and max.)	
CLIMATE	
Modera	е
MMENDATION 1 PRODUCT RECOMMENDATION 2	
LV Super DOT 4 Drauliquid-S DOT 4	

Change every 36000 km/24 months

Change every 1000 km

COOLING SYSTEM Capacity: 2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant -38 Organic NF	Coolant -26	
Change every 36000 km/24 months	;	'

FRONT FORK Capacity: 453 CM3 (each leg)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Fork Oil RR 10	
Change every 12000 km/ 12 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.