

**HONDA CBR CBR 600 RR (2003-2006)****ENGINE/TRANSMISSION**

Capacity: 2,6 liter, Capacity: 3,5 liter (After disassembly), Filter capacity: 0,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Expulsa RR 10W-40</b>	<b>Expulsa 10W-40</b>

*Change every 12000 km/ 12 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Expulsa RR 10W-40</b>	<b>Expulsa 10W-40</b>

*Change every 1000 km***HYDRAULIC BRAKE SYSTEM**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>

*Check every 6000 km/ 12 months, change every 18000 km/ 24 months***COOLING SYSTEM**

Capacity: 3,15 liter (Radiator + engine), Capacity: 0,3 liter (Reserve tank)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>

*Check every 12000 km/ 12 months, change every 36000 km/ 24 months***FRONT FORK**

Capacity: 0,53 liter, Capacity: 0,36 liter (Upside-down front fork)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
<b>Fork Oil RR 10</b>	

*Check every 12000 km/ 12 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.