HONDA CR CR 250 R (2001-2004)



ENGINE		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Tornado	Scoosynth	Maestrol

TRANSMISSION 6 Capacity: 0,85 liter (Dry fill), Capacity: 0,75 liter (Service fill)					
USE		CLIMATE			
Normal		Moderate			
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2				
Expulsa RR 10W-40	Expulsa 10W-40				
01 71 /0		<u>'</u>			

Change every 7 hours/3 races

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			
Change every 24 months		,		

COOLING SYSTEM Capacity: 1,35 liter (Dry fill), Capacity: 1,22 liter (Service fill)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Coolant -38 Organic NF	Coolant -26			
Change every 24 months	·			

FRONT FORK Capacity: 383 CM3		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Fork Oil RR 5		
Change every 7 hours/ 3 races	·	

PRODUCT RECOMMENDATION

HONDA CR CR 250 R (2001-2004)



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.