

HONDA SH SH 150I (2012-2019)**ENGINE**

Capacity: 0,9 liter, Capacity: 0,9 liter (Dry fill), Filter capacity: 0,1 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

FINAL REDUCTION

Capacity: 0,12 liter, Capacity: 0,14 liter (Dry fill)

We are unable to give a standard recommendation for this component. Please contact our service department.

HYDRAULIC BRAKE SYSTEM**USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Drauliquid-LV Super DOT 4****PRODUCT RECOMMENDATION 2****Drauliquid-S DOT 4***Check every 4000 km, change every 24 months***COOLING SYSTEM**

Capacity: 0,48 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant SP 11***Check every 8000 km/ 12 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.